

Price\* : 2,115.00 USD



⚠ Discontinued

## Main

Range of product	Magelis XBTGT
Product or component type	Advanced touchscreen panel
Display type	Backlit colour TFT LCD
Display colour	65536 colours
Display resolution	320 x 240 pixels QVGA
Display size	5.7 inch
Software type	Configuration software
Software designation	Vijeo Designer
Operating system	Magelis
Processor name	CPU RISC
Processor frequency	133 MHz
Memory description	512 kB SRAM back up of data lithium battery 16 MB flash EPROM application memory
Integrated connection type	male SUB-D 9 COM1 serial link RS232C/RS422/RS485 <= 115.2 kbits/s removable screw terminal block power supply RJ45 Ethernet TCP/IP USB type A master port (V1.1) Modicon M340 terminal port communication RJ45 COM2 serial link RS485 <= 187.5 kbit/s
Resistance to electrostatic discharge	6 kV IEC 61000-4-2 level 3
Cut-out dimensions	156 (+ 1/- 0) x 123.5 (+ 1/- 0) mm

## Complementary

Touch sensitive zone	1024 x 1024
Touch panel	Analogue
Backlight lifespan	50000 hours
Brightness	8 levels via touch panel
Character font	Japanese (ANK, Kanji) ASCII (European characters) Chinese (simplified Chinese) Korean Taiwanese (traditional Chinese)
[Us] rated supply voltage	24 V DC
Supply	External source

\* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Supply voltage limits	19.2...28.8 V
Inrush current	30 A
Power consumption in W	26 W
Local signalling	Normal operation or backlighting faulty 1 LED green or orange)
Number of pages	Limited by internal memory capacity
Downloadable protocols	Telemecanique Modicon FIPWAY Telemecanique Modicon Modbus Plus Telemecanique Modicon Modbus TCP/IP Telemecanique Modicon Modbus Mitsubishi Melsec third party protocols Omron Sysmac third party protocols Rockwell Automation Allen-Bradley third party protocols Siemens Simatic third party protocols Telemecanique Modicon Uni-TE
Realtime clock	Built-in
Data storage equipment	1 Compact Flash card >= 1 GB
Use of slot	For 1 fieldbus communication card (Device Net, Profibus DP)
Port Ethernet	10BASE-T/100BASE-TX
Product mounting	Flush mounting
Fixing mode	By 4 screw clamps By 2 spring clips
Front material	Aluminium alloy
Enclosure material	PPT
Marking	CE
Width	6.59 in (167.5 mm)
Height	5.31 in (135 mm)
Maximum Depth	2.34 in (59.5 mm)
Net weight	2.20 lb(US) (1 kg)

## Environment

Immunity to microbreaks	5 ms
Standards	UL 1604 UL 508 EN 61131-2 FCC Class A IEC 61000-6-2 CSA C22.2 No 14
Product certifications	UL Class 1 Division 2 T4A ATEX zone 2/22 CULus CSA Class 1 Division 2 T5 CSA Class 1 Division 2 T4A C-tick UL Class 1 Division 2 T5
Ambient air temperature for operation	32...122 °F (0...50 °C)
Ambient air temperature for storage	-4...140 °F (-20...60 °C)
Relative humidity	0...90 % without condensation
Operating altitude	< 6561.68 ft (2000 m)
IP degree of protection	IP20 IEC 60529 rear panel) IP65 IEC 60529 front panel)
NEMA degree of protection	NEMA 4X front panel (indoor use)
Shock resistance	15 gn 11 ms IEC 60068-2-27
Vibration resistance	1 gn 9...150 Hz)IEC 60068-2-6 3.5 mm 5...9 Hz)IEC 60068-2-6
Resistance to electromagnetic fields	9.14 V/m (10 V/m) IEC 61000-4-3
Resistance to fast transients	2 kV IEC 61000-4-4 level 3

## Ordering and shipping details

Category	22569-MAGELIS XBT-GT (AND XBT-G)
----------	----------------------------------

Discount Schedule	MC2
GTIN	00785901590392
Package weight(Lbs)	2.92 lb(US) (1.323 kg)
Returnability	No
Country of origin	CN

### Packing Units

Package 1 Height	5.51 in (140.000 mm)
Package 1 width	7.24 in (184.000 mm)
Package 1 Length	9.45 in (240.000 mm)

### Contractual warranty

Warranty	18 months
----------	-----------